



## POPLAR PLYWOOD DATA SHEET

### DEFINITION

Poplar plywood is totally made of Poplar veneers. Characteristics of Poplar veneer are: light weight, light color, high homogeneity. Wood is generally white often with a slightly yellowish color.

Poplar plywood is made in accordance with European and International technical regulations in force.

### APPLICATIONS

It's suitable for all those application areas where its features can be enhanced. Poplar plywood is used in Packaging, Furniture, Construction, Retailers, Caravan, Design, Boatbuilding, Wholesale...

### QUALITY CLASSIFICATION

Quality classification follows the indications of EN 635-2 standards. It can be B or BB quality.

### GLUE TYPES in accordance with standard UNI EN 636

- Class 1: for internal use in dry conditions
- Class 3: for external use

TECHNICAL FEATURES	Standard	Unit	Value
Voluminal mass	EN 323	Kg/m <sup>3</sup>	420-480
Modulus of elasticity	EN 310	N/mm <sup>2</sup>	3.500-4.800
Face Screw Holding	EN 320	(kgf)	135
Moisture content	EN 322	%	6-14

### FORMATS

**Dimensions mm.** 2500 x 1220 / 3100 x 1530

Thickness mm	3	4	5	6	7	8	9	10	12	15	18	20	22	25	30	35	40
nº of plies	3	3	3	5	5	5	5	5	7	7	9	9	9	11	13	15	15

### CERTIFICATIONS

On request this product is available with: PEFC certification

**Picó Plywood**  
 Avda. de Espioca 63, 46460, Silla- Valencia (Spain)  
[tableros@picoplywood.com](mailto:tableros@picoplywood.com) , [export@picoplywood.com](mailto:export@picoplywood.com)  
[www.picoplywood.com](http://www.picoplywood.com)

The specific values are average values referred to the normal production. The data provided in this product specification should be used solely as a guide and is of no contractual value. It is responsibility of the customer to determine if Picó's products are suitable for the wished applications and to ensure that places and way of use comply with the supplier's instructions.